

**To / 致:**

Company / 公司: Anhui Daheng Energy  
Technology Co., Ltd.

Contact / 联系人: Mr. Chengyin Jiang  
Email / 邮箱: jiangchengyin@dhsolar.cn

**From / 自:**

Company / 公司: TÜV NORD (HANGZHOU)  
CO., LTD. / 杭州汉德质量认证  
服务有限公司

Contact / 联系人: Ms. Miley Li / 李文颖 小姐  
Email / 邮箱: wli@tuv-nord.com

**Subject: Announcement of cancellation****主题: 证书取消通知**

File No.: PVP04006/21P-04  
项目号:

License holder: **Anhui Daheng Energy Technology Co., Ltd.**  
持证人: No.01, Yaoyuan Road, Luyang District,  
Hefei City, Anhui Province, P.R. China

Certificate No.: 44780 19 406749 - 367R5A1M7  
证书号:

Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules  
产品: 晶硅光伏组件

Herewith it is declared, that the above noted certificate(s) has (have) been invalidated since 2022-07-19.  
特此声明, 上述证书自 2022 年 7 月 19 日起失效。

The cancellation is due to:

取消原因:

License holder applied for cancellation.

持证人申请取消。

New certificate(s) (no: 44 780 19 406749 - 367R6A1M7) has (have) been issued to replace the cancelled one(s).

新证书 (证书号: 44 780 19 406749 - 367R6A1M7) 签发, 取代旧证书。

After the expiry date of the certificate(s), the certificate(s) has (have) not been renewed within 6 months.  
证书到期 6 个月内未续证。

After the expiry date of last factory inspection conclusion, no factory inspection has been conducted or no payment of annual fees has been received within 6 months.

上一厂检结论有效期到期后, 6 个月内未配合厂检或未支付年度费用。

No payment of annual fees has been received within 6 month after last period of payment of annual fees.  
上一证书年费支付期后, 超过 6 个月未支付证书年费。

Others: \_\_\_\_\_

其他情况: \_\_\_\_\_

Please pay attention to stop using the invalid certificate(s) from 2022-07-19. Meanwhile, please send back the original copies of above mentioned certificate(s) to us.

请注意从 2022 年 7 月 19 日开始停止使用无效证书。同时, 请将上述证书原件寄回给我们。

TÜV NORD reserved the right of final explanation about the cancellation of certificate(s). TÜV NORD will not take any responsibility for the circumstance of misusing the invalid certificate(s) by the license holder or the manufacturer.

TÜV NORD 保留对证书取消的最终解释权。TÜV NORD 对证书持有者或制造商滥用无效证书的情况不承担任何责任。

Renewable Energy / 可再生能源

TÜV NORD (Hangzhou) Co., Ltd. / 杭州汉德质量认证服务有限公司

Miley Li / 李文颖



Technical Support / 技术支持

# CERTIFICATE

**TÜV NORD CERT GmbH**  
herewith declares that

**Anhui Daheng Energy Technology Co., Ltd.**  
No.01, Yaoyuan Road, Luyang District,  
Hefei City, Anhui Province,  
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:

**Description of product (details see Annex 2):**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**



Valid from: 2022-07-19

Valid until: 2024-06-13

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC / EN 61215-1:2016; IEC / EN 61215-1-1:2016; IEC 61215-2:2016 / EN 61215-2:2017 + AC:2017 + AC:2018; IEC 61730-1:2016 / EN IEC 61730-1:2018 + AC:2018; IEC 61730-2:2016 / EN IEC 61730-2:2018 + AC:2018.
Registered No.:	44 780 19 406749 - 367R6A1M7
Manufacturer:	see Annex 1
Test Report No.:	492011236.011
File No.:	PVP07021/22P-01



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products



Essen, 2022-07-19

Please also pay attention to the information stated overleaf.

**Anlage 1 zum Zertifikat Nr.:** / *Annex 1 to Certificate No.:* **44 780 19 406749 - 367R6A1M7**

**Seite / Page 1 von / of 1**

**Aktenzeichen:** / *File reference:* **PVP07021/22P-01**

**2022-07-19**

**Manufacturer:**

Manufacturer: **Anhui Daheng Energy Technology Co., Ltd.**  
No.01, Yaoyuan Road, Luyang District,  
Hefei City, Anhui Province, P.R. China

Factory inspection report no.: 862010588.001

**Remark:**

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**

**Description of product(s):**

Module types:

**PV Modules with Mono-crystalline Silicon Solar Cells (156.75mm to 166mm):**

72 cells: DHM72-xxxW (xxx = 325 - 370, in increment of 5)

72 cells: DHM72/FS-xxxW (xxx = 325 - 370, in increment of 5)

60 cells: DHM60-xxxW (xxx = 275 - 310, in increment of 5)

60 cells: DHM60/FS-xxxW (xxx = 275 - 310, in increment of 5)

72 cells: DHM72X-xxxW (xxx= 370 - 390, in increment of 5)

72 cells: DHM72X/FS-xxxW (xxx= 370 - 390, in increment of 5)

60 cells: DHM60X-xxxW (xxx= 310 - 325, in increment of 5)

60 cells: DHM60X/FS-xxxW (xxx= 310 - 325, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

16A

Electrical protection class:

Class II

Pollution degree:

1

Material group:

I

Design load (positive / negative):

3600Pa / 1600Pa

Safety factors:

1.5

Fire safety class:

Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Module types:

**PV Modules with Mono-crystalline Silicon Half-cut Solar Cells (156.75mm to 166mm):**

144 cells: HCM72-xxxW (xxx = 350 - 390, in increment of 5)

144 cells: HCM72/FS-xxxW (xxx = 350 - 390, in increment of 5)

120 cells: HCM60-xxxW (xxx = 290 - 325, in increment of 5)

120 cells: HCM60/FS-xxxW (xxx = 290 - 325, in increment of 5)

156 cells: HCM78X9-xxxW (xxx = 415 - 455, in increment of 5)

156 cells: HCM78X9/FS-xxxW (xxx = 415 - 455, in increment of 5)

144 cells: HCM72X9-xxxW (xxx = 385 - 420, in increment of 5)

144 cells: HCM72X9/FS-xxxW (xxx = 385 - 420, in increment of 5)

120 cells: HCM60X9-xxxW (xxx = 320 - 350, in increment of 5)

120 cells: HCM60X9/FS-xxxW (xxx = 320 - 350, in increment of 5)

144 cells: DHM-72L9-xxxW (xxx = 430 - 465, in increment of 5)

144 cells: DHM-72L9(BW)-xxxW (xxx = 430 - 465, in increment of 5)

144 cells: DHM-72L9(BB)-xxxW (xxx = 430 - 465, in increment of 5)

144 cells: DHM-72L9/FS-xxxW (xxx = 430 - 465, in increment of 5)

144 cells: DHM-72L9/FS(BW)-xxxW (xxx = 430 - 465, in increment of 5)



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products

144 cells: DHM-72L9/FS(BB)-xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF-xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF(BW)-xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF(BB)-xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF/FS -xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF/FS(BW)-xxxW (xxx = 430 - 465, in increment of 5)  
144 cells: DHM-72L9/BF/FS(BB)-xxxW (xxx = 430 - 465, in increment of 5)  
120 cells: DHM-60L9-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9(BW)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9(BB)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/FS-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/FS(BW)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/FS(BB)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF(BW)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF(BB)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF/FS -xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF/FS(BW)-xxxW (xxx = 360 - 385, in increment of 5)  
120 cells: DHM-60L9/BF/FS(BB)-xxxW (xxx = 360 - 385, in increment of 5)

Maximum system voltage: 1500V  
Fuse rating: 20A  
Electrical protection class: Class II  
Pollution degree: 1  
Material group: I  
Design load (positive / negative): 3600Pa / 1600Pa  
Safety factors: 1.5  
Fire safety class: Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Module types: **PV Modules with 182mm Mono-crystalline Silicon Half-cut Solar Cells:**  
156 cells: DHM-78X10-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10(BW)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10(BB)-xxxW (xxx = 570 - 590, in increment of 5)



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products

- 156 cells: DHM-78X10/FS-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/FS(BW)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/FS(BB)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF(BW)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF(BB)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF/FS-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF/FS(BW)-xxxW (xxx = 570 - 590, in increment of 5)  
156 cells: DHM-78X10/BF/FS(BB)-xxxW (xxx = 570 - 590, in increment of 5)  
144 cells: DHM-72X10-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/FS-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/FS(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/FS(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF/FS-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF/FS(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
144 cells: DHM-72X10/BF/FS(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
132 cells: DHM-66X10-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10(BW)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10(BB)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/FS-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/FS(BW)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/FS(BB)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF(BW)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF(BB)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF/FS-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF/FS(BW)-xxxW (xxx = 485 - 505, in increment of 5)  
132 cells: DHM-66X10/BF/FS(BB)-xxxW (xxx = 485 - 505, in increment of 5)  
120 cells: DHM-60X10-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10(BW)-xxxW (xxx = 440 - 460, in increment of 5)



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products

120 cells: DHM-60X10(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/FS-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/FS(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/FS(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF/FS -xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF/FS(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
120 cells: DHM-60X10/BF/FS(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
108 cells: DHM-54X10-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10(BW)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10(BB)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/FS-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/FS(BW)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/FS(BB)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF(BW)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF(BB)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF/FS -xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF/FS(BW)-xxxW (xxx = 395 - 415, in increment of 5)  
108 cells: DHM-54X10/BF/FS(BB)-xxxW (xxx = 395 - 415, in increment of 5)

Maximum system voltage: 1500V  
Fuse rating: 25A  
Electrical protection class: Class II  
Pollution degree: 1  
Material group: I  
Design load (positive / negative): 3600Pa / 1600Pa  
Safety factors: 1.5  
Fire safety class: Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Module types: **PV Modules with 182mm Mono-crystalline Silicon 1/3-cut Solar Cells:**  
216 cells: DHT-M72X10-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10-xxxW (xxx = 525 - 555, in increment of 5)



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products



216 cells: DHM-T72X10(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/FS-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/FS(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/FS(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF/FS -xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF/FS(BW)-xxxW (xxx = 525 - 555, in increment of 5)  
216 cells: DHM-T72X10/BF/FS(BB)-xxxW (xxx = 525 - 555, in increment of 5)  
180 cells: DHT-M60X10-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/FS-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/FS(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/FS(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF(BB)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF/FS -xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF/FS(BW)-xxxW (xxx = 440 - 460, in increment of 5)  
180 cells: DHM-T60X10/BF/FS(BB)-xxxW (xxx = 440 - 460, in increment of 5)

Maximum system voltage: 1500V

Fuse rating: 25A



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products

Electrical protection class:	Class II
Pollution degree:	1
Material group:	I
Design load (positive / negative):	3600Pa / 1600Pa
Safety factors:	1.5
Fire safety class:	Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report.



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**